

MODEL		MGE5800	MGE6700	
ALTERNATOR	Type	Brushless, Revolving Field, Self-exciting, 2-poles, Single phase		
	AC Voltage	50Hz	110V, 220V, 230V, 240V, 110V/220V	
		60Hz	110V, 120V, 220V, 240V, 110V/220V, 120V/240V	
	Max. Output	50Hz	5,000W	5,700W
		60Hz	5,800W	6,700W
	Rated Output	50Hz	4,200W	5,100W
		60Hz	5,000W	5,800W
	Voltage Regulator		Condenser Type, AVR Type (Option)	
	Power Factor		1.0	
DC Output		12V-8.3A (Option)		
ENGINE	Model		GM401PN	
	Type		Air-cooled, 4 cycle, OHV, Gasoline Engine	
	Displacement		391cm ³	
	Fuel		Regular Automobile Gasoline	
	Fuel Tank Capacity		21 L	
	Rated Continuous Operation	50Hz	8.0 h	7.0 h
		60Hz	7.0 h	6.5 h
	Lubricating Oil		Engine Oil SE Class or Higher	
	Lubricating Oil Capacity		1.2 L	
	Starting System		Recoil Starter, Electric Starter (Option)	
DIMENSION	Length x Width x Height		685 x 500 x 500 mm	
	Dry Weight		75 kg	78 kg

Specifications are subject to change without notice.